

**FOR CONCRETE WATER TANKS  
(AND OTHER WET SURFACES)  
"PLASTISET WT" (WATER TANK WATERPROOFING)**

This is a unique composition, manufactured to fill an urgent need for a waterproofing coating which can be used in confined spaces like "Concrete Water Tanks" etc.. Confined spaces do not allow the use of coatings such as "Epoxy" or "Polyurethane", containing organic solvents, on account of danger to the workmen in breathing the vapours. "PLASTISET WT", being a water-based polymer Emulsion, is perfectly safe and has no odour. It can be further thinned down for application by brushing, if required, by adding a limited amount of water to the mixture of "RESIN" and "HARDENER" components, but the pure mixture will give the best results.

"PLASTISET WT", being water based, is compatible with damp surfaces, on which it can be applied, without any further thinning with water. The coating will Polymerise in a few hours, to give a dry surface which can be further painted or plastered in the usual way.

**MIXING RATIO:**

One part of Resin and one part of Hardner by volume. Mix very thoroughly and add a minimum amount of water, to thin down, only if required. Apply by brush. The Brush can be cleaned with hot water if done immediately.

**"PLASTISET WT" IS GUARANTEED TO BE ENTIRELY  
"NON TOXIC AND CAN BE SAFELY USED FOR CONTACT  
WITH DRINKING WATER.**